

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Withdrawn) A device for managing air temperature and/or humidity and/or air quality at a site, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from at least one energy provider through a distribution network, comprising:
 - a processor;
 - a communications channel coupled to the temperature and environment management system and the processor;
 - a display coupled to the processor; and,
 - a control panel coupled to the processor for receiving input from a user and sending the input to the processor, the processor for receiving the input and responsively controlling operation of the temperature and environment management system, the processor for receiving a characteristic of the energy and displaying the characteristic on the display.
2. (Withdrawn) A device, as set forth in claim 1, wherein the characteristic of the energy is related to the availability of the energy.
3. (Withdrawn) A device, as set forth in claim 2, wherein the availability of the energy is related to at least one of the demand for energy. and a cost to the customer site.
4. (Withdrawn) A device, as set forth in claim 1, wherein the characteristic is one of peak or non-peak demand.

5. (Withdrawn) A device, as set forth in claim 1, wherein the characteristic is related to a cost of the energy.

6. (Withdrawn) A device, as set forth in claim 5, wherein the cost is a relative cost.

7. (Withdrawn) A device, as set forth in claim 5, wherein the characteristic is displayed graphically using a symbol.

8. (Withdrawn) A device, as set forth in claim 7, wherein at least one of a color, a size and a number of symbols displayed provides an indication of the characteristic.

9. (Withdrawn) A device, as set forth in claim 1, wherein the display and control panel are implemented in a graphic user interface.

10. (Withdrawn) A device, as set forth in claim 1, wherein the processor is coupled to the energy provider and the characteristic is received from the energy provider.

11. (Currently Amended) A system for managing environmental comfort at a site, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider ~~through a distribution network~~, comprising:

a humidity sensor for sensing humidity at the site;

a temperature sensor for sensing air temperature at the site;

an a thermostatic device in communication with the energy provider to receive a current characteristic of energy, the thermostatic device being coupled to the humidity sensor and the temperature sensor and configured for receiving an input from a user, the input including a temperature setpoint and a selection of one of a plurality of comfort level

scenarios, the thermostatic device for determining an effective setpoint as a function of the temperature setpoint and the sensed humidity and for controlling the temperature and environment management system to maintain air temperature, at the site ~~with~~ within a deadband defined by the effective setpoint and an offset, wherein the offset is based on the selected comfort level scenario and the current characteristic of energy.

12. (Currently Amended) A system, as set forth in claim 11, wherein the thermostatic device includes a processor, a communications channel coupled to the temperature and environment management system, a display coupled to the processor, and a control panel coupled to the processor for receiving the input from the user.

13. (Currently Amended) A system, as set forth in claim 12, wherein the thermostatic device receives ~~a characteristic~~ the current characteristic of the energy and displays the ~~characteristic~~ current characteristic on the display.

14. (Currently Amended) ~~A device~~ system, as set forth in claim 12, wherein the display and control panel are implemented in a graphic user interface.

15. (Currently Amended) A system, as set forth in claim 11, wherein the effective setpoint is equal to the temperature setpoint plus a predetermined number of degrees per a predetermined percentage ~~increase-decrease~~ in relative humidity for cooling applications and the effective setpoint is equal to the temperature setpoint minus a predetermined number of degrees per a predetermined percentage increase in relative humidity for heating applications.

16. (Currently Amended) A system, as set forth in claim 15, wherein the thermostatic device tracks user adjustments to the temperature setpoint and responsively

modifies at least one of the predetermined number of degrees and the predetermined percentage ~~change~~ increase or decrease in relative humidity.

17. (Cancelled)

18. (Cancelled)

19. (Cancelled)

20. (Currently Amended) A system, as set forth in claim 11, wherein the temperature and environment management system includes at least one of a humidifier and a de-humidifier, wherein the thermostatic device controls the at least one of a humidifier and a de-humidifier as function of the effective setpoint, the ~~predetermined~~ offset, and the sensed temperature and humidity.

21. (Withdrawn) A system, as set forth in claim 10, wherein the thermostatic device allows the customer to define a plurality of occupancy modes, each occupancy mode having a user defined temperature setpoint.

22. (Withdrawn) A system, as set forth in claim 21, wherein each occupancy mode includes a default offset.

23. (Withdrawn) A system, as set forth in claim 21, wherein at least one occupancy mode has an associated recovery time, the recovery time being a desired time period in which the system transitions between a previous occupancy mode and the at least one occupancy mode.

24. (Withdrawn) A system, as set forth in claim 23, wherein the thermostatic device allows the user to set at least one start time for the at least one occupancy mode.

25. (Withdrawn) A system, as set forth in claim 24, wherein the system being adapted to transition from the previous occupancy mode to the at least one occupancy mode at a time equal to the at least one start time minus the recovery time.

26. (Withdrawn) A system for managing environmental comfort at a site of a customer, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider through a distribution network, comprising:

a temperature sensor for sensing air temperature at the site; and,

a thermostatic device for receiving a characteristic of the energy, the thermostatic device being coupled to the temperature sensor for receiving input from a user, the input including a temperature setpoint, the thermostatic device for controlling the temperature and environment management system to maintain air temperature at the site as a function of the temperature setpoint, the characteristic, and a pre-selected scenario.

27. (Withdrawn) A system, as set forth in claim 26, wherein the thermostatic device includes a processor, a communications channel coupled to the temperature and environment management system and the processor, a display coupled to the processor, and a control panel coupled to the processor for receiving input from a user and sending the input to the processor, the processor for receiving the input and responsively controlling operation of the temperature and environment management system.

28. (Withdrawn) A system, as set forth in claim 27, wherein the processor is coupled to the energy provider and the characteristic is received from the utility.

29. (Withdrawn) A system, as set forth in claim 26, wherein the characteristic is related to the availability of the energy.

30. (Withdrawn) A system, as set forth in claim 26, wherein the characteristic is related to the cost of the energy.

31. (Withdrawn) A system, as set forth in claim 26, wherein the characteristic is one of a set of characteristics.

32. (Withdrawn) A system, as set forth in claim 26, wherein the set of characteristics includes low, medium, and high.

33. (Withdrawn) A system, as set forth in claim 32, wherein the set of characteristics includes critical.

34. (Withdrawn) A system, as set forth in claim 26, wherein the scenario is related to the customer's willingness to pay for the energy.

35. (Withdrawn) A system, as set forth in claim 26, wherein the pre-selected scenario is one of a set of scenarios.

36. (Withdrawn) A system, as set forth in claim 32, wherein the set of scenarios includes maximum savings, balanced savings and comfort, and maximum comfort.

37. (Withdrawn) A system, as set forth in claim 26, wherein the thermostatic device controls the temperature and environment management system to maintain air temperature at the site with a deadband defined by the temperature setpoint and a

predetermined offset, where the predetermined offset is determined as a function of the characteristic and the scenario.

38. (Withdrawn) A system, as set forth in claim 26, wherein the characteristic is related to the availability of the energy and is one of a set of characteristics and the scenario is related to the customer's willingness to pay and one of a set of scenarios.

39. (Withdrawn) A system, as set forth in claim 38, wherein the set of characteristics includes low, medium, and high and the set of scenarios includes maximum savings, balanced savings and comfort and maximum comfort.

40. (Withdrawn) A system, as set forth in claim 26, wherein the scenario is selected by the customer.

41. (Withdrawn) A system for managing environmental comfort at a site of a customer, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider through a distribution network, comprising:

a temperature sensor for sensing air temperature at the site; and,

a thermostatic device being coupled to the temperature sensor for establishing a thermal gain characteristic of the site and a base line of consumption as a function of the thermal gain characteristic and for receiving input from a user, the input including a temperature setpoint, the thermostatic device for determining for controlling the temperature and environment management system at a demand and consumption rate determined as a function of the temperature setpoint, the characteristic and the base line of consumption.

42. (Withdrawn) A system, as set forth in claim 41, wherein the demand and consumption rate is generally flat.

43. (Withdrawn) A system, as set forth in claim 41, wherein the demand and consumption rate is a relatively reduced rate.

44. (Withdrawn) A method for managing air temperature and/or humidity and/or air quality at a site, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider through a distribution network, comprising:

receiving a characteristic of the energy;

displaying the characteristic of the energy on a display of a thermostatic, device at the site;

receiving input from a user on the thermostatic device; and,

controlling operation of the temperature and environment management system as a function of the user input.

45. (Withdrawn) A method, as set forth in claim 44, wherein the characteristic of the energy is related to the availability of the energy.

46. (Withdrawn) A method, as set forth in claim 44, wherein the characteristic is one of peak or non-peak demand.

47. (Withdrawn) A method, as set forth in claim 44, wherein the characteristic is related to the cost of the energy.

48. (Withdrawn) A method, as set forth in claim 47, wherein the cost is a total cost.

49. (Withdrawn) A method, as set forth in claim 47, wherein the characteristic is displayed graphically using a symbol.

50. (Withdrawn) A method, as set forth in claim 49, at least one of a color, a size and a number of symbols displayed provides an indication of the characteristic.

51. (Withdrawn) A method, as set forth in claim 44, wherein the display and control panel are implemented in a graphic user interface.

52. (Withdrawn) A method, as set forth in claim 44, wherein the characteristic is received from the energy provider.

53. (Currently Amended) A method for managing air quality at a site, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy ~~from an energy provider through a distribution network~~, comprising:

sensing humidity at the site;

sensing air temperature at the site;

receiving a characteristic of energy from the energy provider;

receiving input from a user, the input including a temperature setpoint and a selection of one of a plurality of comfort level scenarios;

determining an effective setpoint as a function of the temperature setpoint and the sensed humidity; and,

determining an offset based on the selected comfort level scenario and the characteristic of energy;

controlling the temperature and environment management system to maintain air temperature at the site with a deadband defined by the effective setpoint and a the ~~predetermined~~ offset.

54. (Currently Amended) A method, as set forth in claim 53, including the steps of ~~receiving a characteristic of the energy and displaying the characteristic of energy~~ on a display.

55. (Currently Amended) A method, as set forth in claim 53, wherein the effective setpoint is equal to the temperature setpoint plus a predetermined number of degrees per a predetermined percentage ~~increase~~ decrease in relative humidity for cooling applications and the effective setpoint is equal to the temperature setpoint minus a predetermined number of degrees per a predetermined percentage increase in relative humidity for heating applications.

56. (Original) A method, as set forth in claim 55, further including the step of tracking user adjustments to the temperature setpoint and responsively modifying at least one of the predetermined number of degrees and the predetermined percentage ~~change~~ increase or decrease in relative humidity.

57. (Cancelled)

58. (Cancelled)

59. (Cancelled)

60. (Currently Amended) A method, as set forth in claim 53, including the step of controlling at least one of a humidifier and a de-humidifier as function of the effective setpoint, the ~~predetermined~~ offset, and the sensed temperature and humidity.

61. (Currently Amended) A method, as set forth in claim 53, including the step of allowing the ~~customer~~user to define a plurality of occupancy modes, each occupancy mode having a user defined temperature setpoint.

62. (Original) A method, as set forth in claim 61, wherein each occupancy mode includes a default-~~offset~~ comfort level scenario.

63. (Currently Amended) A method, as set forth in claim 61, wherein at least one occupancy mode has an associated recovery time, the recovery time being a desired time period in which the temperature and environment management system transitions between a previous occupancy mode and the at least one occupancy mode.

64. (Original) A method, as set forth in claim 63, including the step of allowing the user to set at least one start time for the at least one occupancy mode.

65. (Original) A method, as set forth in claim 64, including the step of transitioning from the previous occupancy mode to the at least one occupancy mode at a time equal to the at least one start time.

66. (Withdrawn) A method for managing air quality at a site of a customer, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider through a distribution network, comprising:

- sensing air temperature at the site; and,
- receiving a characteristic of the energy;
- receiving input from a user, the input including a temperature setpoint; and,

controlling the temperature and environment management system to maintain air temperature at the site as a function of the temperature setpoint, the characteristic, and a pre-selected scenario.

67. (Withdrawn) A method, as set forth in claim 66, wherein the characteristic is received from the energy provider.

68. (Withdrawn) A method, as set forth in claim 66, wherein the characteristic is related to the availability of the energy.

69. (Withdrawn) A method, as set forth in claim 66, wherein the characteristic is related to the cost of the energy.

70. (Withdrawn) A method, as set forth in claim 66, wherein the characteristic is one of a set of characteristics.

71. (Withdrawn) A method, as set forth in claim 66, wherein the set of characteristics includes low, medium, and high.

72. (Withdrawn) A method, as set forth in claim 71, wherein the set of characteristics includes critical.

73. (Withdrawn) A method, as set forth in claim 66, wherein the scenario is related to the customer's willingness to pay for the energy.

74. (Withdrawn) A method, as set forth in claim 66, wherein the pre-selected scenario is one of a set of scenarios.

75. (Withdrawn) A method, as set forth in claim 74, wherein the set of scenarios includes maximum savings, balanced savings and comfort, and maximum comfort.

76. (Withdrawn) A method, as set forth in claim 66, wherein the thermostatic device controls the temperature and environment management system to maintain air temperature at the site with a deadband defined by the temperature setpoint and a predetermined offset, where the predetermined offset is determined as a function of the characteristic and the scenario.

77. (Withdrawn) A method, as set forth in claim 66, wherein the characteristic is related to the availability of the energy and is one of a set of characteristics and the scenario is related to the customer's willingness to pay and one of a set of scenarios.

78. (Withdrawn) A method, as set forth in claim 77, wherein the set of characteristics includes low, medium, and high and the set of scenarios includes maximum savings, balanced savings and comfort and maximum comfort.

79. (Withdrawn) A method, as set forth in claim 78, wherein the set of characteristics further includes critical.

80. (Cancelled)

81. (Withdrawn) A method for managing air quality at a site of a customer, the site having a temperature and environment management system, the temperature and environment management system being supplied with energy from an energy provider through a distribution network, comprising:

sensing air temperature at the site; and,

establishing a thermal gain characteristic of the site and a base line of consumption as a function of the thermal gain characteristic;
receiving input from a user, the input including a temperature setpoint; and,
controlling the temperature and environment management system at a demand and consumption rate determined as a function of the temperature setpoint, the characteristic and the base line of consumption.

82. (Withdrawn) A method, as set forth in claim 81, wherein the demand and consumption rate is generally flat.

83. (Withdrawn) A method, as set forth in claim 81, wherein the demand and consumption rate is a relatively reduced rate.

84. (New) A system, as set forth in claim 11, wherein the characteristic of energy is the cost of energy.

85. (New) A system, as set forth in claim 11, wherein the characteristic of energy includes a plurality of levels including low, medium, high and critical, wherein the offset is determined for each of the characteristic levels of energy within each scenario.

86. (New) A system, as set forth in claim 11, wherein the thermostatic device allows the user to define a plurality of occupancy modes, each occupancy mode having a separate user defined temperature setpoint and selected comfort level scenario.

87. (New) A system, as set forth in claim 86, wherein each occupancy mode includes a default scenario.

88. (New) A system, as set forth in claim 86, wherein at least one occupancy mode has an associated recovery time, the recovery time being a desired time period in which the system transitions between a previous occupancy mode and the at least one occupancy mode.

89. (New) A system, as set forth in claim 86, wherein the thermostatic device allows the user to set at least one start time for at least one occupancy mode.

90. (New) A system, as set forth in claim 89, wherein the system is adapted to transition from the previous occupancy mode to the at least one occupancy mode at a time equal to the at least one start time minus the recovery time.

91. (New) A system, as set forth in claim 11, wherein the comfort level scenarios are related to the user's willingness to pay for the energy.

92. (New) A system, as set forth in claim 91, wherein the plurality of comfort level scenarios includes at least maximum savings, balanced savings and comfort, and maximum comfort.

93. (New) A system, as set forth in claim 92, wherein the comfort level scenario is selected by the energy provider.

94. (New) A system, as set forth in claim 92, wherein the comfort level scenario is selected by the user.

95. (New) A system, as set forth in claim 92, wherein the comfort level scenario is selected by the energy provider and the user selects the temperature setpoint.

96. (New) A system, as set forth in claim 13, wherein the current characteristic of energy is displayed graphically using a symbol.

97. (New) A system, as set forth in claim 13, wherein the current characteristic of energy is displayed using at least one of a color, a size and a number of symbols displayed to provide an indication of the relative cost of energy.

98. (New) A system, as set forth in claim 86, wherein the thermostatic device tracks user adjustments to the temperature setpoint and responsibly modifies at least one of the predetermined number of degrees in the predetermined percentage increase or decrease in relative humidity to adjust the effective setpoint for each of the plurality of occupancy modes.

99. (New) A method, as set forth in claim 53, wherein the characteristic of energy includes a plurality of levels including at least low, medium, high and critical, wherein the offset is determined for each of the characteristic levels of energy with each scenario.

100. (New) A method, as set forth in claim 61, including the step of allowing the user to select one of the comfort level scenarios for each of the plurality of occupancy modes, wherein the offset is determined for each occupancy mode based on the selected comfort level scenario and the characteristic of energy when the temperature and environment management system is operating within the occupancy mode.

101. (New) The method, as set forth in claim 53, wherein the plurality of comfort level scenarios are related to the user's willingness to pay for the energy.

Appln. No. 10/628,518
Amdt dated February 28, 2005
Reply to Office Action of November 17, 2004

102. (New) The method, as set forth in claim 101, wherein the plurality of comfort level scenarios include maximum savings, balanced savings and comfort, and maximum comfort.

103. (New) A method, as set forth in claim 100, wherein the thermostatic device tracks user adjustments to the temperature setpoint and responsibly modifies at least one of the predetermined number of degrees and the predetermined percentage increase or decrease in relative humidity to adjust the effective setpoint for each of the occupancy modes.